



**Cinta  
CLIMAVER®  
STAR**

## CLIMAVER® STAR Accessories

Acrylic-based embossed aluminium tape 75 mm in width and 190 microns in thickness for the realization of **CLIMAVER®** self-supporting ducts in building exteriors.

Ensures the water tightness of the duct and a perfect and permanent adhesion of the tape to the duct.

### EASY INSTALLATION.



Thanks to its flexibility and lightness, it can be installed by a single person without the need for additional tools.

### AIR TIGHTNESS.



It is part of the CLIMAVER® System to ensure the air tightness of the solution.

### USE ON EXTERIOR OF BUILDINGS.



Waterproof and UV protective tape.



CHARACTERISTIC	SYM-BOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD
Presentation	-	-	Multilayer aluminum tape 190 microns in thickness, 75 mm in width and 50 m in length.	-
Operating temperature range	-	°C	-70°C to 149°C	-

## www.isover.es

*This data sheet was completed on the date indicated on the right-hand side and was done with ISOVER's knowledge and experience at that time. However, it does not offer any legal guarantee, unless it has been expressly agreed. Bearing in mind that our knowledge and developments of building solutions and products are continuously evolving, ensure that when you use this data sheet, it is the latest version. The description of the product applications does not take into account the special circumstances that may arise for a specific case. Please check that this product is the appropriate one for the application you are considering. For more detailed information, contact our network of ISOVER branches.*

SAINT-GOBAIN ISOVER IBÉRICA, S.L. • C/ Príncipe de Vergara, 132 • 28002 Madrid • Spain

APR-2024