





Isoover glass wool blanket covered by a face with a steam barrier with double aluminum coating (aluminum + black aluminum) that acts as support and steam barrier. Climcover® Roll Alu1 Black is reinforced with a tridirectional glass mesh and has a overlapping tongue that guarantees the continuity of the steam barrier.

Due to its high thermal performance, Climcover Roll Alu1 Black, it is the appropriate solution for the isolation by the outside of air distribution duct networks, both of rectangular and circular section, in facilities seen.



## **AESTHETICS.**

Its black finish is perfect for exposed installations.



## **FAST INSTALLATION.**

Solution designed to adapt to all types of metal conduits.



## THERMAL INSULATION.

High thermal insulation  $\lambda(10^{\circ}\text{C})~0.032~\text{W/(m.K)}$ 



## FIRE REACTION.

Euroclass A1.



### **RECYCLED GLASS.**

Sustainable product. Made with 80% recycled glass.



# CLIMCOVER® Roll Alu1 Black



CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES					
Reaction to fire			Euroclass A1					
Characteristics	-		CLIMCOVER* Roll Alu 1 Black incorporates a tiapima for optimal sealing of the joints between insulation sections. Thanks to the reinforced coating with glass mesh, the installation of an additional metal mesh is not necessary. Avoid condensation in metal ducts.					
Thermal resistance	R (25mm)	m²K/W	0,78	0,74	0,68	0,64	0,61	
Thermal conductivity	Т	ōС	10	20	40	50	60	
	λ	W/(mK)	0,032	0,034	0,037	0,039	0,041	

DELIVERY FORM: STANDARD DIMENSIONS / PACKAGING INFORMATION									
Thickness d (mm)	Length I (m)	Width b (m)	m²/pack	m²/pallet	m²/truck	Designation code			
25	10.00	1.15	19.44	388.80	6998	MW-EN 14303-T2-MV1			

#### www.isover.es

This data sheet was completed on the date indicated on the right-hand side and was done with ISOVER's knowledge and experience at that time. However, it does not offer any legal guarantee, unless it has been expressly agreed. Bearing in mind that our knowledge and developments of building solutions and products are continuously evolving, ensure that when you use this data sheet, it is the latest version. The description of the product applications does not take into account the special circumstances that may arise for a specific case. Please check that this product is the appropriate one for the application you are considering. For more detailed information, contact our network of ISOVER branches.



