CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-003.0-06

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations
(details cf. annex)

Placed on the market under the name or trade mark of

SAINT-GOBAIN ISOVER G+H AG
Bürgermeister-Grünzweig-Str.1
67059 Ludwigshafen
Germany

and produced in the manufacturing plant

Speyer
Industriestraße 125
67346 Speyer
Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 17.02.2014 and will remain valid (but no longer than 02.12.2021) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 02.12.2020

Forschungsinstitut für Wärmeschutz e.V. München · FIW München · www.fiw-muenchen.de · 2020

Certification Body

Ralph Alberti

Dipl.-Ing. Ralph Alberti

Forschungsinstitut für Wärmeschutz e.V. München
Lochhamer Schlag 4 · 82166 Gräfelfing · Germany
Telephone +49 (0)89 85800-0 · Telefax +49 (0)89 85800-41
info@fiw-muenchen.de · www.fiw-muenchen.de

Forschungsinstitut für Wärmeschutz e. V. München
Annex to Certificate of Constancy of Performance: 0751-CPR.2-003.0-06
Date: 02.12.2020

Factory:	Speyer, Industriestraße 125, 67346 Speyer, Germany
Construction product(s):	Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013
Intended use:	Thermal insulation products for building equipment and industrial installations
Level(s) or class(es) reaction to fire:	for uses subject to regulations on reaction to fire A1/A2. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.
Attestation of conformity system:	1

	Product			Reaction to fire EN 13501-1				
No.	Form	Name	Description	Nominal density	Classi-fication	Range	Fire Group	Classification report
1	Roll	**FT/AGF**	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	14 kg/m³ - 22 kg/m³	A1	Organic content: 4,8 %	6	KB-Hoch-141181
2	Roll	**FT**	Roll made of non-combustible mineral wool	15 kg/m³ - 22 kg/m³	A1	Organic content: 6,4 %	3	KB-Hoch -130032
3	Roll	**FE**	Roll made of non-combustible mineral wool	19 kg/m³	A1	Organic content: 6,4 %	3	KB-Hoch -130032
4	Roll	**FE/AGF**	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	19 kg/m³	A1	Organic content: 4,8 %	6	KB-Hoch-141181
5	Slab	**P4/GW**	Slab made of non-combustible mineral wool	23 kg/m³	A1	Organic content: 6,4 %	3	KB-Hoch -130032
6	Roll	**FK**	Roll made of non-combustible mineral wool	24 kg/m³	A1	Organic content: 6,4 %	3	KB-Hoch -130032
7	Roll	**FK/AGF**	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	24 kg/m³	A1	Organic content: 6,4 %	3	KB-Hoch -130032

Forschungsinstitut für Wärmeschutz e.V. München
FIW München
www.fiw-muenchen.de • 2520 •

	Product				Reaction to fire EN 13501-1			
No.	Form	Name	Description	Nominal density	Classi-fication	Range	Fire Group	Classification report
8	Roll	**FK/G-H**	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	24 kg/m³	A1	Organic content: 4,8 %	6	KB-Hoch-141181
9	Slab	**PF 28**	Slab made of non-combustible mineral wool	28 kg/m³	A1	-	4	230008616/6
10	Roll	**FI**	Roll made of non-combustible mineral wool	30 kg/m³	A1	-	4	230008616/6
11	Lamella mat	**ISOVER Lamellenmatten ML 3** **CLIMCOVER Lamella Mat**	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminium foil	27 kg/m³	A1	Organic content: 4,8 %	6	KB-Hoch-141181
12	Lamella mat	**ISOVER Druckfeste Lamellenmatten ML_DT** **Tech Lamella Mat 2.0**	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminum foil	48 kg/m³	A1	Organic content: 5,4 %	10	KB-Hoch-170365

Detail information about the insulation products are given in the classification reports

Gräfelfing 02.12.2020

Forschungsinstitut für Wärmeschutz e.V. München · www.fiw-muenchen.de · 2020 ·

Certification Body

Dipl.-Ing. Ralph Alberti