



# ULTIMATE Protect Accessories

## Fire Protect Screws - Helical Screws

Stainless-steel helical shaped screws. Assembly of **ULTIMATE PROTECT SLAB**. Used to connect the longitudinal joints between panels, inserting the screw at a 45° angle. Additional pastes are not required. The length of the screw must be twice the thickness of the panel.



### Presentation

Boxes of 200 units, containing lengths 60, 80, 120, 140, 160, 180 and 200 mm.

## Protect BSK Adhesivo Inorgánico

Non-flammable inorganic adhesive with an alkaline sodium silicate base. When a duct passes through a wall, it is applied to join the borders of the panel or **Ultimate Protect** mat to the wall, to finish the system sealing.



### Presentation

Box of 12 310 ml cartridges. 15kg bucket.

## Protect BSF Intumescent Paste

Aqueous-based intumescent product, white, pH neutral and solvent free. When a duct passes through a wall, it is applied to create a flame-retardant seal in the gap between the wall and the duct.



### Presentation

Box of 12 310 ml cartridges. 15kg bucket.

## U Protect Black Alu Tape

90 mm wide black aluminum tape, water resistant with modified solvent-free acrylic adhesive.



### Presentation

Black aluminum roll 90 mm wide and 100 metre long.